

Safety Data Sheet



Epoxy WB Fast – PART A

1. PRODUCT AND COMPANY IDENTIFICATION

24 HOUR EMERGENCY ASSISTANCE	MANUFACTURER/GENERAL MSDS ASSISTANCE
CHEM-TEL 1-800-255-3924	ONYX CONCRETE COATINGS Tel.: (888)-497-3872 1610 E. Miraloma Ave. Placentia, CA 92870

PRODUCT IDENTIFIER/NAME: Epoxy WB Fast – PART A
RECOMMENDED USE: Chemical intermediate for epoxy

2. HAZARD(S) IDENTIFICATION

HAZARD CLASSIFICATION:

Skin Sensitizer Category 1

NFPA ratings (scale 0 – 4):

HEALTH	2
FIRE	1
REACTIVITY	0
SPECIAL	-

NFPA HAZARD RATING:

4= EXTREME 2= MODERATE 0= INSIGNIFICANT
3= HIGH 1= SLIGHT



HAZARD PICTOGRAMS:

SIGNAL WORD: Warning

PHYSICAL APPEARANCE: White milky liquid with slight amine odor.

HAZARD STATEMENTS:

May cause an allergic skin reaction.

PRECAUTIONARY STATEMENTS:

Prevention: Avoid breathing dust/fume/gas/mist/vapors/spray. Contaminated work clothing should not be allowed out of the workplace. Wear protective gloves.

Response: IF ON SKIN: Wash with plenty of soap and water. If skin irritation or rash occurs: Get medical advice/attention. Wash contaminated clothing before reuse.

Disposal: Disposal of contents/container to be specified in accordance with regulations.

HAZARDS NOT OTHERWISE CLASSIFIED:

Mild eye irritant.

May cause sensitization by skin contact.

3.92% of mixture consists of ingredients of unknown acute toxicity

3. COMPOSITION/INFORMATION ON INGREDIENTS

Components	CAS Number	Concentration
<i>Oxirane, 2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bis-, homopolymer</i>	(CAS 25085-99-8)	50% - 60%
<i>Water</i>	(CAS 7732-18-5)	40% - 60%

CHEMICAL FAMILY: Dispersion

4. FIRST AID MEASURES

GENERAL ADVICE: Seek medical advice. If breathing has stopped or is labored, give assisted respirations. Supplemental oxygen may be indicated. If the heart has stopped, trained personnel should begin cardiopulmonary resuscitation immediately.

EYE CONTACT: Rinse immediately with plenty of water also under the eyelids for at least 20 minutes. Remove contact lenses.

SKIN CONTACT: Wash off immediately with plenty of water for at least 20 minutes. Take off contaminated clothing and shoes immediately.

Avoid prolonged or repeated contact to skin. Wash thoroughly after handling.

INGESTION: Never give anything by mouth to an unconscious person. Prevent aspiration of vomit. Turn victim's head to the side

INHALATION: Move to fresh air.

MOST IMPORTANT SYMPTOMS/EFFECTS: Skin disorders and allergies.

TREATMENT: NOTE TO PHYSICIANS: Application of corticosteroid cream has been effective in treating skin irritation.

5. FIRE-FIGHTING MEASURES

SUITABLE EXTINGUISHING MEDIA: Alcohol-resistant foam. Carbon dioxide (CO₂). Dry chemical. Dry sand. Limestone powder.

FIRE-FIGHTING EQUIPMENT: Use personal protective equipment. Wear self-contained breathing apparatus for firefighting if necessary.

SPECIFIC HAZARDS: Incomplete combustion may form carbon monoxide. Burning produces noxious and toxic fumes. Downwind personnel must be evacuated.

6. ACCIDENTAL RELEASE MEASURES

PERSONAL PRECAUTIONS: Wear suitable protective clothing, gloves and eye/face protection. Evacuate personnel to safe areas.

ENVIRONMENTAL PRECAUTIONS: Construct a dike to prevent spreading.

METHODS FOR CLEANING UP: Approach suspected leak areas with caution. Place in appropriate chemical waste container.

ADDITIONAL SAFETY PROCAUTIONS: Open enclosed spaces to outside atmosphere. If possible, stop flow of product.

7. HANDLING AND STORAGE

HANDLING: Emergency showers and eye wash stations should be readily accessible. Adhere to work practice rules established by government regulations. Avoid contact with eyes. Spraying increases the risk of hazardous exposure. In atmospheres where the material is sprayed, workers should avoid contact with aerosols. Use personal protective equipment. When using, do not eat, drink or smoke.

STORAGE: Keep away from Oxidizers. Keep containers tightly closed in a dry, cool and well-ventilated place.

TECHNICAL MEASURE: Keep from freezing.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

ENGINEERING MEASURES: Provide readily accessible eye wash stations and safety showers. Provide natural or explosion-proof ventilation adequate to ensure concentrations are kept below exposure limits.

PERSONAL PROTECTIVE EQUIPMENT:

RESPIRATORY PROTECTION: Wear appropriate respirator when ventilation is inadequate. Spraying increases the risk of hazardous exposure. In atmospheres where the material is sprayed, workers should avoid contact with aerosols through proper engineering controls such as exhaust ventilation and/or proper protective equipment such as a full-face-air-supplied respirators.

HAND PROTECTION: PVC disposable gloves. Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.

EYE PROTECTION: Chemical safety glasses.

SKIN AND BODY PROTECTION: No specific recommendation.

SPECIAL INSTRUCTION FOR PROTECTION: Provide readily accessible eye wash stations and safety showers. Wash at the end of each work shift and before eating, smoking or using the toilet.

9. PHYSICAL AND CHEMICAL PROPERTIES

BOILING POINT: 212°F, 100°C

FLASH POINT: >480°F, >248°C

VAP PRESSURE: 19.30mmHg @ 21°C

SOL. IN WATER: Insoluble.

SP. GRAVITY: 1.11

APPEARANCE: White, liquid

ODOR: No data available

pH: Neutral

10. STABILITY AND REACTIVITY

CHEMICAL STABILITY: Stable under normal conditions.

CONDITIONS TO AVOID: No data available

MATERIALS TO AVOID: Oxidizing agents.

HAZARDOUS DECOMPOSITION PRODUCTS: Chlorine
Carbon monoxide.
Carbon dioxide (CO₂).

11. TOXICOLOGICAL INFORMATION

Likely routes of exposure

Effects on Eye: Contact with eyes may cause irritation.

Effects on Skin: No data available.

Inhalation Effects: This product presents an elevated inhalation health risk when used in spray or aerosol applications.

Ingestion Effects: No data available.

Symptoms: No data available.

ACUTE TOXICITY

Acute Oral Toxicity: No data is available on the product itself.

Inhalation: No data is available on the product itself.

Acute Dermal Toxicity: No data is available on the product itself.

Skin corrosion/irritation: Non-irritant to the skin of a rabbit.

Serious eye damage/eye Irritation: Mild eye irritation.

Sensitization: May cause sensitization by skin contact.

Chronic toxicity or effects from long term exposures

Carcinogenicity: No data available.

Reproductive toxicity: No data is available on the product itself.

Germ cell mutagenicity: No data is available on the product itself.

Specific target organ systemic toxicity (single exposure): No data available.

Specific target organ systemic toxicity (repeated exposure): No data available.

Aspiration hazard: No data available.

Delayed and Immediate Effects and Chronic Effects from Short- and Long-Term Exposure

This product contains no listed carcinogens according to IARC, ACGIH, NTP and/or OSHA in concentrations of 0.1 percent or greater. May cause allergic skin reaction. Skin disorders and Allergies.

12. ECOLOGICAL INFORMATION

ECOTOXICITY EFFECTS

AQUATIC TOXICITY: No data is available on the product itself.

TOXICITY TO OTHER ORGANISMS: No data available.

PERSISTANCE AND DEGRADABILITY

BIODEGRADABILITY: No data is available on the product itself.

MOBILITY: No data available.

BIOACCUMULATION: No data is available on the product itself.

13. DISPOSAL CONSIDERATIONS

WASTE FROM RESIDUES: Contact supplier if guidance is required.

CONTAMINATED PACKAGING: Dispose of container and unused contents in accordance with federal, state, and local requirements.

14. TRANSPORT INFORMATION

Transportation Emergency Number: CHEMTEL 1-800-255-3924.

DOT

Not dangerous goods

IATA

Not dangerous goods

IMDG

Not dangerous goods

TGF

Not dangerous goods

Further Information: Not classified as dangerous in the meaning of transport regulations. The transportation information is not intended to convey all specific regulatory data relating to this material.

15. REGULATORY INFORMATION

TOXIC SUBSTANCE CONTROL ACT (TSCA) 12(b) COMPONENT(S): None.

EPA SARA Title III SECTION 312 (40 CFR 370) HAZARD CLASSIFICATION: Acute Health Hazard

EPA SARA Title III SECTOPM 313 (40 CFR 372) COMPONENT(S) ABOVE "DE MINIMUS" LEVEL:
None.

U.S. CALIFORNIA PROP 65: This product does not contain any chemicals known to State of California to cause cancer, birth defects or any other harm.

16. OTHER INFORMATION

Date Revised: 06/09/2016

MANUFACTURER'S NAME AND ADDRESS:

ONYX CONCRETE COATINGS

1610 E. Miraloma Ave.

Placentia, CA 92870

Telephone: 714-572-6723

The information herein is given in good faith, but no warranty expressed or implied is made. Onyx Concrete Coatings urges users of this product to evaluate its suitability and compliance with local regulations as Onyx cannot foresee the nature of the final application or final location of usage.

Safety Data Sheet



Epoxy WB Fast – PART B

1. PRODUCT AND COMPANY IDENTIFICATION

24 HOUR EMERGENCY ASSISTANCE	MANUFACTURER/GENERAL MSDS ASSISTANCE
CHEM-TEL 1-800-255-3924	ONYX CONCRETE COATINGS Tel.: (888)-497-3872 1610 E. Miraloma Ave. Placentia, CA 92870

PRODUCT IDENTIFIER/NAME: Epoxy WB Fast – PART B
RECOMMENDED USE: Chemical intermediate for epoxy

2. HAZARD(S) IDENTIFICATION

HAZARD CLASSIFICATION:

Skin Irritation Category 2
Serious Eye Damage Category 1

NFPA ratings (scale 0 – 4):

HEALTH	2
FIRE	1
REACTIVITY	0
SPECIAL	-

NFPA HAZARD RATING:

4= EXTREME 2= MODERATE 0= INSIGNIFICANT
3= HIGH 1= SLIGHT



HAZARD PICTOGRAMS:

SIGNAL WORD: Danger

PHYSICAL APPEARANCE: Milky white or colored liquid with faint epoxy odor

HAZARD STATEMENTS:

Causes skin irritation.
Causes serious eye damage.

PRECAUTIONARY STATEMENTS:

Prevention: Wash hands thoroughly after handling. Wear protective gloves/protective clothing/eye protection/face protection.

Response:

IF SWALLOWED: rinse mouth. Do NOT induce vomiting.

IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or doctor/physician. Wash contaminated clothing before reuse.

Storage:

Store locked up.

Disposal:

Disposal of contents/container to be specified in accordance with regulations.

HAZARDS NOT OTHERWISE CLASSIFIED:

Components of the product may affect the nervous system.

Severe eye irritant.

Moderate skin irritant.

Moderate respiratory irritant.

39.6% of mixture consists of ingredients of unknown acute toxicity

3. COMPOSITION/INFORMATION ON INGREDIENTS

<i>Poly[oxy(methyl-1,2-ethanediyl)], .alpha.-(2-aminomethylethyl)-.omega.-(2-aminomethylethoxy)-</i>	(CAS 9046-10-0)	< 10%
<i>Propan-2-ol, 1-methoxy-</i>	(CAS 107-98-2)	< 5%
Benzyl Alcohol	(CAS 100-51-6)	1% - 5%

CHEMICAL FAMILY: Polyamine Emulsion. The remaining components are trade secret.

This document is prepared pursuant to the OSHA Hazard Communication Standard (29 CFR 1910.1200). In addition, other substances not Hazardous per this OSHA Standard may be listed. Where proprietary Ingredient shows, the identity may be made available as provided in this standard.

4. FIRST AID MEASURES

GENERAL ADVICE: Seek medical advice. If breathing has stopped or is labored, give assisted respirations. Supplemental oxygen may be indicated. If the heart has stopped, trained personnel should begin cardiopulmonary resuscitation immediately.

EYES: Rinse immediately with plenty of water for at least 15 minutes.

SKIN: Immediately remove contaminated clothing and any extraneous chemical, if possible, to do so without delay.

INGESTION: Never give anything by mouth to an unconscious person. If a person vomits when lying on his back, place him in the recovery position. Prevent aspiration of vomit. Turn victim's head to the side.

INHALATION: If breathing has stopped or is labored, give assisted respirations. Supplemental oxygen may be indicated. If the heart has stopped, trained personnel should begin cardiopulmonary resuscitation immediately. Move to fresh air.

MOST IMPORTANT SYMPTOMS/EFFECTS: Repeated and/or prolonged exposure to low concentrations of vapors and/or aerosols may cause: Sore throat, Neurological disorders, Eye disease, Skin disorders, and Allergies/Asthma

5. FIRE-FIGHTING MEASURES

METHOD USED: PMCC

FLAMMABLE LIMITS

LFL: Not applicable

UFL: Not applicable

EXTINGUISHING MEDIA: Alcohol-resistant foam, Carbon dioxide (CO₂), Dry chemical, Dry sand, Limestone Powder

SPECIFIC HAZARDS: May generate ammonia gas. May generate toxic nitrogen oxide gases. Use of water may result in the formation of very toxic aqueous solutions. Do not allow run-off from firefighting to enter drains or water courses. Incomplete combustion may form carbon monoxide. Burning produces noxious and toxic fumes. Downwind personnel must be evacuated.

FIRE-FIGHTING EQUIPMENT: Use personal protective equipment. Wear self-containing breathing apparatus for firefighting if necessary.

6. ACCIDENTAL RELEASE MEASURES

PERSONAL PRECAUTIONS: Use self-contained breathing apparatus and chemically protective clothing. Wear suitable protective clothing, gloves and eye/face protection. Evacuate personnel to safe areas.

ENVIRONMENTAL PRECAUTIONS: Construct a dike to prevent spreading. Construct a dike to prevent spreading.

METHODS FOR CLEANING UP: Approach suspected leak areas with caution. Place in appropriate chemical waste container.

ADDITIONAL ADVICE: Open enclosed spaces to outside atmosphere. If possible, stop flow of product.

7. HANDLING AND STORAGE

SPECIAL PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE: Do not store near acids. Keep away from Oxidizers. Keep containers tightly closed in a dry, cool and well-ventilated place. Do not store in reactive metal containers. Keep from freezing.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

ENGINEERING MEASURES:

Provide readily accessible eye wash stations and safety showers.

Provide natural or explosion-proof ventilation adequate to ensure concentrations are kept below exposure limits.

PERSONAL PROTECTIVE EQUIPMENT:

Respiratory Protection:

Wear appropriate respirator when ventilation is adequate.

Hand Protection: PVC disposable gloves. Impervious gloves. Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk

Eye Protection: Chemical resistant goggles must be worn.

Skin and Body Protection: Long sleeve shirts and trousers without cuffs.

Environmental Exposure Controls: Construct a dike to prevent spreading.

Special Instructions for Protection and Hygiene: Provide readily accessible eye wash stations and safety showers. Wash hands at the end of each work shift and before eating, smoking, or using the toilet.

EXPOSURE LIMITS:

Propan-2-ol, 1-methoxy- Time Weighted Average (TWA): ACGIH 50 ppm -

Propan-2-ol, 1-methoxy- Short Term Exposure Limit (STEL): ACGIH 100 ppm -

Propan-2-ol, 1-methoxy- Recommended exposure limit (REL): NIOSH 100 ppm 360 mg/m³

Propan-2-ol, 1-methoxy- Short Term Exposure Limit (STEL): NIOSH 150 ppm 540 mg/m³

Propan-2-ol, 1-methoxy- Time Weighted Average (TWA): OSHA Z1A 100 ppm 360 mg/m³

Propan-2-ol, 1-methoxy- Short Term Exposure Limit (STEL): OSHA Z1A 150 ppm 540 mg/m³

Propan-2-ol, 1-methoxy- Time Weighted Average (TWA) Permissible

Exposure Limit (PEL): US CA OEL

100 ppm 360 mg/m³

Propan-2-ol, 1-methoxy- Short Term Exposure Limit (STEL): US CA OEL 150 ppm 540 mg/m³

Propan-2-ol, 1-methoxy- Time Weighted Average (TWA): ACGIH NIC 50 ppm -

Propan-2-ol, 1-methoxy- Short Term Exposure Limit (STEL): ACGIH NIC 100 ppm -

Propan-2-ol, 1-methoxy- Time Weighted Average (TWA): TN OEL 100 ppm 380 mg/m³

Propan-2-ol, 1-methoxy- Short Term Exposure Limit (STEL): TN OEL 150 ppm 540 mg/m³

Benzyl alcohol Time Weighted Average (TWA): WEEL 10 ppm 44.20 mg/m³

9. PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE: Liquid, White
ODOR THRESHOLD: No data available
MELTING POINT: No data available
BOILING POINT: 205°F (96°C)
FLASH POINT: >212°F (>100°C)
EVAPORATION RATE: No data available
VAP PRESS: 18.70 mmHg at 21 °C
VAP DENSITY: Not applicable
SOL. IN WATER: Dispersible
DENSITY: 1.08 g/cm³
ODOR: Slight
pH: 10.6

10. STABILITY AND REACTIVITY

Chemical Stability: Stable under normal conditions.

Conditions to avoid: No data available.

Materials to avoid:

Sodium hypochlorite.

Organic acids (i.e., acetic acid, citric acid etc.).

Mineral acids.

Incompatible with bases.

Reaction with peroxides may result in violent decomposition of peroxide possibly creating an explosion.

Oxidizing agents.

Reactive metals (e.g., sodium, calcium, zinc etc.).

Materials reactive with hydroxyl compounds.

Hazardous decomposition products:

Nitrogen oxides (NO_x).

Nitrogen oxide can react with water vapors to form corrosive nitric acid.

Chlorine

Carbon monoxide.

Carbon dioxide (CO₂).

Ammonia

Aldehydes

Flammable hydrocarbon fragments.

11. TOXICOLOGICAL INFORMATION

LIKELY ROUTES OF EXPOSURE:

Effects on Eye: Severe eye irritation.

Effects on Skin: If absorbed through the skin, may cause central nervous system effects, such as headache, nausea, dizziness, confusion, breathing difficulties. Causes skin irritation.

Inhalation Effects: May cause central nervous system effects, such as headache, nausea, dizziness, confusion, breathing difficulties. Severe cases of overexposure can result in respiratory failure. May cause nose, throat, and lung irritation.

Inhalation of vapors and/or aerosols in high concentration may cause irritation of respiratory system.

Ingestion Effects: May cause central nervous system effects, such as headache, nausea, vomiting, abdominal pain, dizziness, confusion, breathing difficulties. Severe cases of overexposure can result in respiratory failure.

Symptoms: Repeated and/or prolonged exposure to low concentrations of vapors and/or aerosols may cause: Sore throat. Neurological disorders, Eye disease., Skin disorders and Allergies., Asthma.

ACUTE TOXICITY:

Acute Oral Toxicity: No data is available on the product itself.

Acute Oral Toxicity – Components:

**Poly[oxy(methyl-1,2-ethanediyl)],
.alpha.-(2-aminomethylethyl)-.omega.-**

(2-aminomethylethoxy)-

LD50 : 2,880 mg/kg Species : Rat.

Propan-2-ol, 1-methoxy-

LD50 : 5,700 mg/kg Species : Rat.

Benzyl alcohol

LD50 : 1,230 mg/kg Species : Rat.

Inhalation : No data is available on the product itself.

Inhalation – Components:

Propan-2-ol, 1-methoxy-

LC50 (4 h) : 22 mg/l Species : Rat.

Benzyl alcohol

LC50 (4 h) : > 4.178 mg/l OECD Test Guideline 403 Species : Rat.

Acute Dermal Toxicity: No data is available on the product itself.

Acute Dermal Toxicity – Components:

Poly[oxy(methyl-1,2-ethanediyl)],

.alpha.-(2-aminomethylethyl)-.omega.-

(2-aminomethylethoxy)-

LD50 : 2,980 mg/kg Species : Rabbit.

Propan-2-ol, 1-methoxy-

LD50 : 13,000 mg/kg Species : Rabbit.

Benzyl alcohol

LD50 : 2,000 mg/kg Species : Rabbit.

Skin corrosion/irritation: Moderate skin irritation. Non-corrosive in an in vitro test.

Serious eye damage/eye irritation: Severe eye irritation.

Sensitization: No data available.

CHRONIC TOXICITY:

Carcinogenicity: No data available.

Reproductive toxicity: No data is available on the product itself.

Germ cell mutagenicity: No data is available on the product itself.

Specific target organ systemic toxicity (single exposure): No data available.

Specific target organ systemic toxicity (repeated exposure): No data available.

Aspiration hazard: No data available.

Delayed and Immediate Effects and Chronic Effects from Short- and Long-Term Exposure

This product contains no listed carcinogens according to IARC, ACGIH, NTP and/or OSHA in concentrations of 0.1 percent or greater. Neurological disorders, Eye disease., Skin disorders and Allergies., Asthma.

Rats exposed orally to 800 mg/kg benzyl alcohol for thirteen weeks exhibited CNS depression and histopathological changes in the brain, thymus and skeletal muscles. The No Observed Adverse Effect Level (NOAEL) was 400 mg/kg. No evidence of carcinogenicity was seen in a two-year study with rats and mice.

12. ECOLOGICAL INFORMATION

ECOTOXICITY EFFECTS

Aquatic toxicity: No data is available on the product itself.

Toxicity to fish – Components:

Propan-2-ol, 1-methoxy-

LC50 (96 h) : > 4,600 mg/l Species : Golden orfe (Leuciscus idus).

Propan-2-ol, 1-methoxy-

LC50 (96 h) : 20,800 mg/l Species : Fathead minnow (Pimephales promelas).

Benzyl alcohol

LC50 (96 h) : 10 mg/l Species : Bluegill sunfish (Lepomis macrochirus).

Benzyl alcohol

LC50 (96 h) : 460 mg/l Species : Fathead minnow (Pimephales promelas).

Toxicity to daphnia – Components:

Propan-2-ol, 1-methoxy-

EC50 (48 h) : > 500 mg/l Species : Daphnia

Toxicity to algae – Components:

Benzyl alcohol

IC50 (72 h) : 700 mg/l Species : Algae.

Toxicity to other organisms: No data available.

PERSISTENCE AND DEGRADABILITY

Biodegradability: No data is available on the product itself.

Mobility: No data available.

Bioaccumulation: No data is available on the product itself.

Bioaccumulation – Components:

Propan-2-ol, 1-methoxy-

Negligible bioaccumulation potential.

Benzyl alcohol

Low bioaccumulation potential.

13. DISPOSAL CONSIDERATIONS

WASTE FROM RESIDUES: Contact supplier if guidance is required.

CONTAMINATED PACKAGING: Dispose of container and unused contents in accordance with federal, state, and local requirements.

14. TRANSPORT INFORMATION

Transportation Emergency Number: CHEMTEL 1-800-255-3924.

DOT

Not dangerous goods

IATA

Not dangerous goods

IMDG

Not dangerous goods

TDG

Not dangerous goods

Further Information

Not classified as dangerous in the meaning of transport regulations. The transportation information is not intended to convey all specific regulatory data relating to this material.

15. REGULATORY INFORMATION

TOXIC SUBSTANCE CONTROL ACT (TSCA) 12(b) COMPONENT(S): None

EPA SARA Title III SECTION 312 (40 CFR 370) HAZARD CLASSIFICATION: Acute Health Hazard

CALIFORNIA PROP 65: This product does not contain any chemicals known to State of California to cause cancer, birth defects or any other harm.

16. OTHER INFORMATION

Date Revised: 06/09/2016

MANUFACTURER'S NAME AND ADDRESS:

ONYX CONCRETE COATINGS

1610 E. Miraloma Ave.

Placentia, CA 92870

Telephone: 714-572-6723

Country	Regulatory list	Notification
USA	TSCA	Included on Inventory.
EU	EINECS	EU Included on EINECS inventory or polymer substance, monomers included on EINECS inventory or no longer polymer.
Canada	DSL	Included on Inventory.
Australia	AICS	Included on Inventory.
Japan	ENCS	Included on Inventory.
South Korea	ECL	Included on Inventory.
China	SEPA	Included on Inventory.
Philippines	PICCS	Included on Inventory.

The information herein is given in good faith, but no warranty expressed or implied is made. Onyx Concrete Coatings urges users of this product to evaluate its suitability and compliance with local regulations as Onyx cannot foresee the nature of the final application or final location of usage.